



# Strong performance spot light for retrofit MR16 halogen spots

## MASTER LEDspot LV

Delivering intense accent beam, MASTER LEDspot LV is an ideal retrofit solution for spot lighting. MASTER LEDspot LV is designed to replace halogen or incandescent spots. It realizes natural colors, enables cozy and comfortable ambience for residential, hospitality and emphasizes the beauty of merchandise in retail. New smaller housing provides perfect fitting with majority of luminaires in a market with a MR16 GU 5.3 holder. It not only employs Philips' patented solution to guarantee the broadest possible compatibility with standard 12V halogen electronic transformers, it also delivers high beam intensity which is equivalent to halogen MR16 spots. The dimming function enables to create the desired atmosphere and it works with broad selection of dimmers. Its high SDCM ensure stricter color consistency, that is maintained over product life. MASTER LEDspot LV delivers huge energy savings and minimizes maintenance cost without any compromise on light quality and lifetime, enabling residential and business owners to achieve a return on their investment within short period time.

### Benefits

- High intensity of beam for accent lighting in professional applications
- Strong brightness maintained over time
- More natural colors realised for cozy ambience for hospitality and better merchandise display in retail application

# MASTER LEDspot LV


## Features

- High intensity of beam equivalent to halogen spots
- Better color realisation with high CRI value, and strong color consistency over time
- Clearly defined beam spread for accent lighting
- Compatible with an extensive range of transformers and smooth dimming for dimmable products
- High lumen maintenance with long lifetime up to 40,000 hours

## Application

- Home: Living room, bed room, hall way
- Hospitality: Hotel guest room, corridors, lobby, reception area, restaurant, bars, cafes
- Retail: Exhibitions, display cabinets, shops, dressing room, check out area

## Dimensional drawing



Product	D	C
MASTER LED 6.5-50W 927 MR16 10D Dim	50 mm	46.5 mm
MASTER LED 6.5-50W 927 MR16 24D Dim	50 mm	
MASTER LED 6.5-50W 927 MR16 36D Dim	50 mm	
MASTER LED 6.5-50W 927 MR16 60D Dim	50 mm	46.5 mm
MASTER LED 6.5-50W 930 MR16 10D Dim	50 mm	46.5 mm
MASTER LED 6.5-50W 930 MR16 24D Dim	50 mm	46.5 mm
MASTER LED 6.5-50W 930 MR16 36D Dim	50 mm	46.5 mm
MASTER LED 6.5-50W 930 MR16 60D Dim	50 mm	46.5 mm
MASTER LED 6.5-50W 940 MR16 36D Dim	50 mm	46.5 mm
MASTER LED 6.5-50W 940 MR16 60D Dim	50 mm	46.5 mm

MASTER LEDspot LV



General Information	
Cap-Base	GU5.3
Switching Cycle	50,000
Nominal lifetime	40,000 hour(s)
Light Technical	
Color rendering index (CRI)	90
LLMF At End Of Nominal Lifetime (Nom)	70 %
Operating and Electrical	
Input Frequency	- Hz
Line Frequency	- Hz
Power Consumption	6.5 W
Starting Time (Nom)	0.5 s
Wattage Equivalent	50 W
Temperature	
T-Case Maximum (Nom)	90 °C
Controls and Dimming	
Dimmable	Only with specific dimmers
Mechanical and Housing	
Bulb Shape	MR16

Light Technical (1/2)



Order Code	Full Product Name	Beam Angle (Nom)	Correlated Color		
			Temperature (Nom)	Color Code	Luminous Flux
929003071908	MASTER LED 6.5-50W 927 MR16 24D Dim	24 degree(s)	2700 K	927	500 lm
929003072008	MASTER LED 6.5-50W 930 MR16 24D Dim	24 degree(s)	3000 K	930	500 lm
929003072208	MASTER LED 6.5-50W 927 MR16 36D Dim	36 degree(s)	2700 K	927	500 lm
929003072308	MASTER LED 6.5-50W 930 MR16 36D Dim	36 degree(s)	3000 K	930	500 lm
929003072408	MASTER LED 6.5-50W 940 MR16 36D Dim	36 degree(s)	4000 K	940	530 lm
929003071608	MASTER LED 6.5-50W 927 MR16 10D Dim	10 degree(s)	2700 K	927	500 lm
929003071708	MASTER LED 6.5-50W 930 MR16 10D Dim	10 degree(s)	3000 K	930	500 lm
929003075908	MASTER LED 6.5-50W 927 MR16 60D Dim	60 degree(s)	2700 K	927	500 lm
929003076008	MASTER LED 6.5-50W 930 MR16 60D Dim	60 degree(s)	3000 K	930	500 lm
929003076108	MASTER LED 6.5-50W 940 MR16 60D Dim	60 degree(s)	4000 K	940	530 lm

Light Technical (2/2)


Order Code	Full Product Name	Luminous Intensity (Nom)
929003071908	MASTER LED 6.5-50W 927 MR16 24D Dim	2,800 cd
929003072008	MASTER LED 6.5-50W 930 MR16 24D Dim	2,800 cd
929003072208	MASTER LED 6.5-50W 927 MR16 36D Dim	1,400 cd
929003072308	MASTER LED 6.5-50W 930 MR16 36D Dim	1,600 cd
929003072408	MASTER LED 6.5-50W 940 MR16 36D Dim	1,600 cd
929003071608	MASTER LED 6.5-50W 927 MR16 10D Dim	5,300 cd
929003071708	MASTER LED 6.5-50W 930 MR16 10D Dim	5,300 cd
929003075908	MASTER LED 6.5-50W 927 MR16 60D Dim	500 cd
929003076008	MASTER LED 6.5-50W 930 MR16 60D Dim	500 cd
929003076108	MASTER LED 6.5-50W 940 MR16 60D Dim	550 cd




MASTER LEDspot LV




Accent Diagrams



Accent Diagram - MASTER LED 6.5-50W 930  
MR16 24D Dim




Accent Diagram - MASTER LED 6.5-50W 930  
MR16 36D Dim




Accent Diagram - MASTER LED 6.5-50W 930  
MR16 10D Dim


Accent Diagrams




Accent Diagram - MASTER LED 6.5-50W 927  
MR16 24D Dim




Accent Diagram - MASTER LED 6.5-50W 927  
MR16 10D Dim




Accent Diagram - MASTER LED 6.5-50W 940  
MR16 36D Dim



Accent Diagram - MASTER LED 6.5-50W 927  
MR16 36D Dim




Accent Diagram - MASTER LED 6.5-50W 927  
MR16 60D Dim




Accent Diagram - MASTER LED 6.5-50W 940  
MR16 60D Dim


Beam Diagrams



Beam diagram - MASTER LED 6.5-50W 940  
MR16 36D Dim




Beam diagram - MASTER LED 6.5-50W 930  
MR16 36D Dim




Beam diagram - MASTER LED 6.5-50W 927  
MR16 60D Dim


Beam Diagrams




Beam diagram - MASTER LED 6.5-50W 927 MR16 10D Dim




Beam diagram - MASTER LED 6.5-50W 927 MR16 24D Dim




Beam diagram - MASTER LED 6.5-50W 930 MR16 10D Dim



Beam diagram - MASTER LED 6.5-50W 927 MR16 36D Dim



Beam diagram - MASTER LED 6.5-50W 930 MR16 24D Dim



Beam diagram - MASTER LED 6.5-50W 940 MR16 60D Dim

